An Introduction to the Z Shell

Paul Falstad
pfalstad@phoenix.princeton.edu

zsh is a shell designed for interactive use, although it is also a powerful scripting language. Many of the useful features of bash, ksh, and tcsh were incorporated into zsh; many original features were added. This document details some of the unique features of zsh. It assumes basic knowledge of the standard UNIX shells; the intent is to show a reader already familiar with one of the other major shells what makes zsh more useful or more powerful. This document is not at all comprehensive; read the manual entry for a description of the shell that is complete and concise, although somewhat overwhelming and devoid of examples.

Filename Generation

Otherwise known as *globbing*, filename generation is quite extensive in zsh. Of course, it has all the basics:

```
% ls
Makefile   file.pro   foo.o      main.o     q.c        run234     stuff
bar.o      foo        link       morestuff  run123     run240     sub
file.h     foo.c      main.h     pipe       run2       run303
% ls *.c
foo.c  q.c
% ls *.[co]
bar.o   foo.c   foo.o   main.o  q.c
% ls foo.?
foo.c  foo.o
% ls *.[^c]
bar.o   file.h  foo.o   main.h  main.o
% ls *.[^oh]
foo.c  q.c
```

Also, if the *EXTENDEDGLOB* option is set, some new features are activated. For example, the ^ character negates the pattern following it:

```
% setopt extendedglob
% ls -d ^*.c
Makefile   file.pro   link       morestuff  run2       run303
bar.o      foo        main.h     pipe       run234     stuff
file.h     foo.o      main.o     run123     run240     sub
% ls -d ^*.*
Makefile   link       pipe       run2       run240     stuff
foo        morestuff  run123     run234     run303     sub
% ls -d ^Makefile
bar.o      foo        link       morestuff  run123     run240     sub
file.h     foo.c      main.h     pipe       run2       run303
file.pro   foo.o      main.o     q.c        run234     stuff
% ls -d *.^c
.rhosts   bar.o     file.h    file.pro  foo.o     main.h    main.o
```

An expression of the form <*x*–*y*> matches a range of integers:

```
% ls run<200-300>
run234  run240
% ls run<300-400>
run303
% ls run<-200>
run123  run2
% ls run<300->
run303
% ls run<>
run123  run2    run234  run240  run303
```

Grouping is possible:

```
% ls (foo|bar).*
bar.o  foo.c  foo.o
% ls *.(c|o|pro)
bar.o     file.pro  foo.c     foo.o     main.o    q.c
```

Also, the string `****/` forces a recursive search of subdirectories:

```
% ls -R
Makefile   file.pro   foo.o      main.o     q.c        run234     stuff
bar.o      foo        link       morestuff  run123     run240     sub
file.h     foo.c      main.h     pipe       run2       run303

morestuff:

stuff:
file  xxx   yyy

stuff/xxx:
foobar

stuff/yyy:
frobar
% ls ****/*bar
stuff/xxx/foobar  stuff/yyy/frobar
% ls ****/f*
file.h            foo               foo.o             stuff/xxx/foobar
file.pro          foo.c             stuff/file        stuff/yyy/frobar
% ls *bar*
bar.o
% ls ****/*bar*
bar.o             stuff/xxx/foobar  stuff/yyy/frobar
% ls stuff/****/*bar*
stuff/xxx/foobar  stuff/yyy/frobar
```

It is possible to exclude certain files from the patterns using the ~ character. A pattern of the form `*.c~bar.c` lists all files matching `*.c`, except for the file `bar.c`.

```
% ls *.c
foo.c    foob.c    bar.c
% ls *.c~bar.c
foo.c    foob.c
% ls *.c~f*
bar.c
```

One can add a number of *qualifiers* to the end of any of these patterns, to restrict matches to certain file types. A qualified pattern is of the form

pattern(...)

with single-letter qualifiers inside the parentheses.

```
% alias l='ls -dF'
% l *
Makefile    foo*        main.h      q.c         run240
bar.o       foo.c       main.o      run123      run303
file.h      foo.o       morestuff/  run2        stuff/
file.pro    link@       pipe        run234      sub
% l *(/)
morestuff/  stuff/
% l *(@)
link@
% l *(*)
foo*        link@       morestuff/  stuff/
% l *(x)
foo*        link@       morestuff/  stuff/
% l *(X)
foo*        link@       morestuff/  stuff/
% l *(R)
bar.o       foo*        link@       morestuff/  run123      run240
file.h      foo.c       main.h      pipe        run2        run303
file.pro    foo.o       main.o      q.c         run234      stuff/
```

Note that *(x) and *(*) both match executables. *(X) matches files executable by others, as opposed to *(x), which matches files executable by the owner. *(R) and *(r) match readable files; *(W) and *(w), which checks for writable files. *(W) is especially important, since it checks for world-writable files:

```
% l *(w)
bar.o       foo*        link@       morestuff/  run123      run240
file.h      foo.c       main.h      pipe        run2        run303
file.pro    foo.o       main.o      q.c         run234      stuff/
% l *(W)
link@   run240
% l -l link run240
lrwxrwxrwx  1 pfalstad       10 May 23 18:12 link -> /bin/false*
-rw-rw-rw-  1 pfalstad        0 May 23 18:12 run240
```

You can filter out the symbolic links with the ^ character:

```
% l *(W^@)
run240
% l *(x)
foo*        link@       morestuff/  stuff/
% l *(x^@/)
foo*
```

To find all plain files, you can use .:

```
% l *(.)
Makefile  file.h    foo*      foo.o     main.o    run123    run234    run303
bar.o     file.pro  foo.c     main.h    q.c       run2      run240    sub
% l *(^.)
link@       morestuff/  pipe        stuff/
% l s*(.)
stuff/   sub
% l *(p)
pipe
% l -l *(p)
prw-r--r--  1 pfalstad        0 May 23 18:12 pipe
```

`*(U)` matches all files owned by you. To search for all files not owned by you, use `*(^U)`:

```
% l -l *(^U)
-rw-------  1 subbarao       29 May 23 18:13 sub
```

This searches for setuid files:

```
% l -l *(s)
-rwsr-xr-x  1 pfalstad       16 May 23 18:12 foo*
```

This checks for a certain user's files:

```
% ypmatch subbarao passwd
subbarao:*:3338:35:Kartik Subbarao:/u/subbarao:/usr/princeton/bin/zsh
% l -l *(u3338)
-rw-------  1 subbarao       29 May 23 18:13 sub
```

Startup Files

There are five startup files that zsh will read commands from:

```
$ZDOTDIR/.zshenv
$ZDOTDIR/.zprofile
$ZDOTDIR/.zshrc
$ZDOTDIR/.zlogin
$ZDOTDIR/.zlogout
```

If **ZDOTDIR** is not set, then the value of **HOME** is used; this is the usual case.

`.zshenv` is sourced on all invocations of the shell, unless the `-f` option is set. It should contain commands to set the command search path, plus other important environment variables. `.zshenv` should not contain commands that produce output or assume the shell is attached to a tty.

`.zshrc` is sourced in interactive shells. It should contain commands to set up aliases, functions, options, key bindings, etc.

`.zlogin` is sourced in login shells. It should contain commands that should be executed only in login shells. `.zlogout` is sourced when login shells exit. `.zprofile` is similar to `.zlogin`, except that it is sourced before `.zshrc`. `.zprofile` is meant as an alternative to `.zlogin` for ksh fans; the two are not intended to be used together, although this could certainly be done if desired. `.zlogin` is not the place for alias definitions, options, environment variable settings, etc.; as a general rule, it should not change the shell environment at all. Rather, it should be used to set the terminal type and run a series of external commands (`fortune`, `msgs`, etc).

Shell Functions

zsh also allows you to create your own commands by defining shell functions. For example:

```
% yp () {
>       ypmatch $1 passwd.byname
> }
% yp pfalstad
pfalstad:*:3564:35:Paul John Falstad:/u/pfalstad:/usr/princeton/bin/zsh
```

This function looks up a user in the NIS password map. The `$1` expands to the first argument to `yp`. The function could have been equivalently defined in one of the following ways:

```
% function yp {
>       ypmatch $1 passwd.byname
> }
% function yp () {
>       ypmatch $1 passwd.byname
> }
% function yp () ypmatch $1 passwd.byname
```

Note that aliases are expanded when the function definition is parsed, not when the function is executed. For example:

```
% alias ypmatch=echo
% yp pfalstad
pfalstad:*:3564:35:Paul John Falstad:/u/pfalstad:/usr/princeton/bin/zsh
```

Since the alias was defined after the function was parsed, it has no effect on the function's execution. However, if we define the function again with the alias in place:

```
% function yp () { ypmatch $1 passwd.byname }
% yp pfalstad
pfalstad passwd.byname
```

it is parsed with the new alias definition in place. Therefore, in general you must define aliases before functions.

We can make the function take multiple arguments:

```
% unalias ypmatch
% yp () {
>       for i
>       do ypmatch $i passwd.byname
>       done
> }
% yp pfalstad subbarao sukthnkr
pfalstad:*:3564:35:Paul John Falstad:/u/pfalstad:/usr/princeton/bin/zsh
subbarao:*:3338:35:Kartik Subbarao:/u/subbarao:/usr/princeton/bin/zsh
sukthnkr:*:1267:35:Rahul Sukthankar:/u/sukthnkr:/usr/princeton/bin/tcsh
```

The `for i` loops through each of the function's arguments, setting `i` equal to each of them in turn. We can also make the function do something sensible if no arguments are given:

```
% yp () {
>       if (( $# == 0 ))
>       then echo usage: yp name ...; fi
>       for i; do ypmatch $i passwd.byname; done
> }
% yp
usage: yp name ...
% yp pfalstad sukthnkr
pfalstad:*:3564:35:Paul John Falstad:/u/pfalstad:/usr/princeton/bin/zsh
sukthnkr:*:1267:35:Rahul Sukthankar:/u/sukthnkr:/usr/princeton/bin/tcsh
```

$# is the number of arguments supplied to the function. If it is equal to zero, we print a usage message; otherwise, we loop through the arguments, and `ypmatch` all of them.

Here's a function that selects a random line from a file:

```
% randline () {
>       integer z=$(wc -l <$1)
>       sed -n $[RANDOM % z + 1]p $1
> }
% randline /etc/motd
PHOENIX WILL BE DOWN briefly Friday morning, 5/24/91 from 8 AM to
% randline /etc/motd
SunOS Release 4.1.1 (PHOENIX) #19: Tue May 14 19:03:15 EDT 1991
% randline /etc/motd
| Please use the "msgs" command to read announcements.  Refer to the   |
% echo $z

%
```

`randline` has a local variable, `z`, that holds the number of lines in the file. `$[RANDOM % z + 1]` expands to a random number between 1 and `z`. An expression of the form `$[...]` expands to the value of the arithmetic expression within the brackets, and the **RANDOM** variable returns a random number each time it is referenced. `%` is the modulus operator, as in C. Therefore, `sed -n $[RANDOM%z+1]p` picks a random line from its input, from 1 to `z`.

Function definitions can be viewed with the `functions` builtin:

```
% functions randline
randline () {
        integer z=$(wc -l <$1)
        sed -n $[RANDOM % z + 1]p $1

}
% functions
yp () {
        if let $# == 0

        then
                echo usage: yp name ...

        fi
        for i
        do
                ypmatch $i passwd.byname

                done

}
randline () {
        integer z=$(wc -l <$1)
        sed -n $[RANDOM % z + 1]p $1

}
```

Here's another one:

```
% cx () { chmod +x $* }
% ls -l foo bar
-rw-r--r--  1 pfalstad       29 May 24 04:38 bar
-rw-r--r--  1 pfalstad       29 May 24 04:38 foo
% cx foo bar
% ls -l foo bar
-rwxr-xr-x  1 pfalstad       29 May 24 04:38 bar
-rwxr-xr-x  1 pfalstad       29 May 24 04:38 foo
```

Note that this could also have been implemented as an alias:

```
% chmod 644 foo bar
% alias cx='chmod +x'
% cx foo bar
% ls -l foo bar
-rwxr-xr-x  1 pfalstad       29 May 24 04:38 bar
-rwxr-xr-x  1 pfalstad       29 May 24 04:38 foo
```

Instead of defining a lot of functions in your `.zshrc`, all of which you may not use, it is often better to use the `autoload` builtin. The idea is, you create a directory where function definitions are stored, declare the names in your `.zshrc`, and tell the shell where to look for them. Whenever you reference a function, the shell will automatically load it into memory.

```
% mkdir /tmp/funs
% cat >/tmp/funs/yp
ypmatch $1 passwd.byname
^D
% cat >/tmp/funs/cx
chmod +x $*
^D
% FPATH=/tmp/funs
% autoload cx yp
% functions cx yp
undefined cx ()
undefined yp ()
% chmod 755 /tmp/funs/{cx,yp}
% yp egsirer
egsirer:*:3214:35:Emin Gun Sirer:/u/egsirer:/bin/sh
% functions yp
yp () {
        ypmatch $1 passwd.byname
}
```

This idea has other benefits. By adding a `#!` header to the files, you can make them double as shell scripts. (Although it is faster to use them as functions, since a separate process is not created.)

```
% ed /tmp/funs/yp
25
i
#! /usr/local/bin/zsh
w
42
q
% </tmp/funs/yp
#! /usr/local/bin/zsh
ypmatch $1 passwd.byname
% /tmp/funs/yp sukthnkr
sukthnkr:*:1267:35:Rahul Sukthankar:/u/sukthnkr:/usr/princeton/bin/tcsh
```

Now other people, who may not use zsh, or who don't want to copy all of your `.zshrc`, may use these functions as shell scripts.

Directories

One nice feature of zsh is the way it prints directories. For example, if we set the prompt like this:

```
phoenix% PROMPT='%~> '
~> cd src
~/src>
```

the shell will print the current directory in the prompt, using the `~` character. However, zsh is smarter than most other shells in this respect:

```
~/src> cd ~subbarao
~subbarao> cd ~maruchck
~maruchck> cd lib
~maruchck/lib> cd fun
~maruchck/lib/fun> foo=/usr/princeton/common/src
~maruchck/lib/fun> cd ~foo
~foo> cd ..
/usr/princeton/common> cd src
~foo> cd news/nntp
~foo/news/nntp> cd inews
~foo/news/nntp/inews>
```

Note that zsh prints *other* users' directories in the form `~user`. Also note that you can set a parameter and use it as a directory name; zsh will act as if `foo` is a user with the login directory `/usr/princeton/common/src`. This is convenient, especially if you're sick of seeing prompts like this:

```
phoenix:/usr/princeton/common/src/X.V11R4/contrib/clients/xv/docs>
```

If you get stuck in this position, you can give the current directory a short name, like this:

```
/usr/princeton/common/src/news/nntp/inews> inews=$PWD
/usr/princeton/common/src/news/nntp/inews> echo ~inews
/usr/princeton/common/src/news/nntp/inews
~inews>
```

When you reference a directory in the form `~inews`, the shell assumes that you want the directory displayed in this form; thus simply typing `echo ~inews` or `cd ~inews` causes the prompt to be shortened. You can define a shell function for this purpose:

```
~inews> namedir () { $1=$PWD ;  : ~$1 }
~inews> cd /usr/princeton/bin
/usr/princeton/bin> namedir pbin
~pbin> cd /var/spool/mail
/var/spool/mail> namedir spool
~spool> cd .msgs
~spool/.msgs>
```

You may want to add this one-line function to your `.zshrc`.

zsh can also put the current directory in your title bar, if you are using a windowing system. One way to do this is with the `chpwd` function, which is automatically executed by the shell whenever you change directory. If you are using xterm, this will work:

```
chpwd () { print -Pn '^[]2;%~^G' }
```

The `-P` option tells `print` to treat its arguments like a prompt string; otherwise the `%~` would not be

expanded. The `-n` option suppresses the terminating newline, as with `echo`.

If you are using an IRIS `wsh`, do this:

```
chpwd () { print -Pn '^[P1.y%~^[´ }
```

The `print -D` command has other uses. For example, to print the current directory to standard output in short form, you can do this:

```
% print -D $PWD
~subbarao/src
```

and to print each component of the path in short form:

```
% print -D $path
/bin /usr/bin ~locbin ~locbin/X11 ~/bin
```

Directory Stacks

If you use csh, you may know about directory stacks. The `pushd` command puts the current directory on the stack, and changes to a new directory; the `popd` command pops a directory off the stack and changes to it.

```
phoenix% cd
phoenix% PROMPT='Z %~> '
Z ~> pushd /tmp
/tmp ~
Z /tmp> pushd /usr/etc
/usr/etc /tmp ~
Z /usr/etc> pushd /usr/bin
/usr/bin /usr/etc /tmp ~
Z /usr/bin> popd
/usr/etc /tmp ~
Z /usr/etc> popd
/tmp ~
Z /tmp> pushd /etc
/etc /tmp ~
Z /etc> popd
/tmp ~
```

zsh's directory stack commands work similarly. One difference is the way `pushd` is handled if no arguments are given. As in csh, this exchanges the top two elements of the directory stack:

```
Z /tmp> dirs
/tmp ~
Z /tmp> pushd
~ /tmp
```

unless the stack only has one entry:

```
Z ~> popd
/tmp
Z /tmp> dirs
/tmp
Z /tmp> pushd
~ /tmp
```

or unless the *PUSHDTOHOME* option is set:

```
Z ~> setopt pushdtohome
Z ~> pushd
~ ~ /tmp
```

As an alternative to using directory stacks in this manner, we can get something like a *directory history* by setting a few more options and parameters:

```
~> DIRSTACKSIZE=8
~> setopt autopushd pushdminus pushdsilent pushdtohome
~> alias dh='dirs -v'
~> cd /tmp
/tmp> cd /usr
/usr> cd bin
/usr/bin> cd ../pub
/usr/pub> dh
0       /usr/pub
1       /usr/bin
2       /usr
3       /tmp
4       ~
/usr/pub> cd -3
/tmp> dh
0       /tmp
1       /usr/pub
2       /usr/bin
3       /usr
4       ~
/tmp> ls =2/df
/usr/bin/df
/tmp> cd -4
~>
```

Note that `=2` expanded to the second directory in the history list, and that `cd -3` recalled the third directory in the list.

You may be wondering what all those options do. *AUTOPUSHD* made `cd` act like `pushd`. (`alias cd=pushd` is not sufficient, for various reasons.) *PUSHDMINUS* swapped the meaning of `cd +1` and `cd -1`; we want them to mean the opposite of what they mean in csh, because it makes more sense in this scheme, and it's easier to type:

```
~> dh
0       ~
1       /tmp
2       /usr/pub
3       /usr/bin
4       /usr
~> unsetopt pushdminus
~> cd +1
/tmp> dh
0       /tmp
1       ~
2       /usr/pub
3       /usr/bin
4       /usr
/tmp> cd +2
/usr/pub>
```

PUSHDSILENT keeps the shell from printing the directory stack each time we do a `cd`, and *PUSHDTOHOME* we mentioned earlier:

```
/usr/pub> unsetopt pushdsilent
/usr/pub> cd /etc
/etc /usr/pub /tmp ~ /usr/bin /usr
/etc> cd
~ /etc /usr/pub /tmp ~ /usr/bin /usr
~> unsetopt pushdtohome
~> cd
/etc ~ /usr/pub /tmp ~ /usr/bin /usr
/etc>
```

DIRSTACKSIZE keeps the directory stack from getting too large, much like *HISTSIZE*:

```
/etc> setopt pushdsilent
/etc> cd /
/> cd /
/> cd /
/> cd /
/> cd /
/> cd /
/> cd /
/> cd /
/> dh
0       /
1       /
2       /
3       /
4       /
5       /
6       /
7       /
```

Command/Process Substitution

Command substitution in zsh can take two forms. In the traditional form, a command enclosed in backquotes (‘...‘) is replaced on the command line with its output. This is the form used by the older shells. Newer shells (like zsh) also provide another form, `$(...)`. This form is much easier to nest.

```
% ls -l ‘echo /vmunix‘
-rwxr-xr-x  1 root      1209702 May 14 19:04 /vmunix
% ls -l $(echo /vmunix)
-rwxr-xr-x  1 root      1209702 May 14 19:04 /vmunix
% who | grep mad
subbarao ttyt7   May 23 15:02   (mad55sx15.Prince)
pfalstad ttyu1   May 23 16:25   (mad55sx14.Prince)
subbarao ttyu6   May 23 15:04   (mad55sx15.Prince)
pfalstad ttyv3   May 23 16:25   (mad55sx14.Prince)
% who | grep mad | awk ’{print $2}’
ttyt7
ttyu1
ttyu6
ttyv3
% cd /dev; ls -l $(who |
> grep $(echo mad) |
> awk ’{ print $2 }’)
crwx-w----  1 subbarao  20,  71 May 23 18:35 ttyt7
crw--w----  1 pfalstad  20,  81 May 23 18:42 ttyu1
crwx-w----  1 subbarao  20,  86 May 23 18:38 ttyu6
crw--w----  1 pfalstad  20,  99 May 23 18:41 ttyv3
```

Many common uses of command substitution, however, are superseded by other mechanisms of zsh:

```
% ls -l ‘tty‘
crw-rw-rw-  1 root      20,  28 May 23 18:35 /dev/ttyqc
% ls -l $TTY
crw-rw-rw-  1 root      20,  28 May 23 18:35 /dev/ttyqc
% ls -l ‘which rn‘
-rwxr-xr-x  1 root       172032 Mar  6 18:40 /usr/princeton/bin/rn
% ls -l =rn
-rwxr-xr-x  1 root       172032 Mar  6 18:40 /usr/princeton/bin/rn
```

A command name with a `=` prepended is replaced with its full pathname. This can be very convenient. If it’s not convenient for you, you can turn it off:

```
% ls
=foo    =bar
% ls =foo =bar
zsh: foo not found
% setopt noequals
% ls =foo =bar
=foo    =bar
```

Another nice feature is process substitution:

```
% who | fgrep -f =(print -l root lemke shgchan subbarao)
root     console May 19 10:41
lemke    ttyq0   May 22 10:05   (narnia:0.0)
lemke    ttyr7   May 22 10:05   (narnia:0.0)
lemke    ttyrd   May 22 10:05   (narnia:0.0)
shgchan  ttys1   May 23 16:52   (gaudi.Princeton.)
subbarao ttyt7   May 23 15:02   (mad55sx15.Prince)
subbarao ttyu6   May 23 15:04   (mad55sx15.Prince)
shgchan  ttyvb   May 23 16:51   (gaudi.Princeton.)
```

A command of the form `=(...)` is replaced with the name of a *file* containing its output. (A command substitution, on the other hand, is replaced with the output itself.) `print -l` is like `echo`, excepts that it prints its arguments one per line, the way `fgrep` expects them:

```
% print -l foo bar
foo
bar
```

We could also have written:

```
% who | fgrep -f =(echo ’root
> lemke
> shgchan
> subbarao’)
```

Using process substitution, you can edit the output of a command:

```
% ed =(who | fgrep -f ~/.friends)
355
g/lemke/d
w /tmp/filbar
226
q
% cat /tmp/filbar
root     console May 19 10:41
shgchan  ttys1   May 23 16:52   (gaudi.Princeton.)
subbarao ttyt7   May 23 15:02   (mad55sx15.Prince)
subbarao ttyu6   May 23 15:04   (mad55sx15.Prince)
shgchan  ttyvb   May 23 16:51   (gaudi.Princeton.)
```

or easily read archived mail:

```
% mail -f =(zcat ~/mail/oldzshmail.Z)
"/tmp/zsha06024": 84 messages, 0 new, 43 unread
>  1  U  TO: pfalstad, zsh (10)
   2  U  nytim!tim@uunet.uu.net, Re: Zsh on Sparc1 /SunOS 4.0.3
   3  U  JAM%TPN@utrcgw.utc.com, zsh fix (15)
   4  U  djm@eng.umd.edu, way to find out if running zsh? (25)
   5  U  djm@eng.umd.edu, Re: way to find out if running zsh? (17)
   6   r djm@eng.umd.edu, Meta . (18)
   7  U  jack@cs.glasgow.ac.uk, Re: problem building zsh (147)
   8  U  nytim!tim@uunet.uu.net, Re: Zsh on Sparc1 /SunOS 4.0.3
   9     ursa!jmd, Another fix... (61)
  10  U  pplacewa@bbn.com, Re: v18i084: Zsh 2.00 - A small complaint (36)
  11  U  lubkin@cs.rochester.edu, POSIX job control (34)
  12  U  yale!bronson!tan@uunet.UU.NET
  13  U  brett@rpi.edu, zsh (36)
  14  S  subbarao, zsh sucks!!!! (286)
  15  U  snibru!d241s008!d241s013!ala@relay.EU.net, zsh (165)
  16  U  nytim!tim@uunet.UU.NET, Re: Zsh on Sparc1 /SunOS 4.0.3
  17  U  subbarao, zsh is a junk shell (43)
  18  U  amaranth@vela.acs.oakland.edu, zsh (33)
43u/84 1: x
% ls -l /tmp/zsha06024
/tmp/zsha06024 not found
```

Note that the shell creates a temporary file, and deletes it when the command is finished.

```
% diff =(ls) =(ls -F)
3c3
< fortune
---
> fortune*
10c10
< strfile
---
> strfile*
```

If you read zsh's man page, you may notice that `<(...)` is another form of process substitution which is similar to `=(...)`. There is an important difference between the two. In the `<(...)` case, the shell creates a named pipe (FIFO) instead of a file. This is better, since it does not fill up the file system; but it does not work in all cases. In fact, if we had replaced `=(...)` with `<(...)` in the examples above, all of them would have stopped working except for `fgrep -f <(...)`. You can not edit a pipe, or open it as a mail folder; `fgrep`, however, has no problem with reading a list of words from a pipe. You may wonder why `diff <(foo) bar` doesn't work, since `foo | diff - bar` works; this is because `diff` creates a temporary file if it notices that one of its arguments is `-`, and then copies its standard input to the temporary

file.

Aliasing

Often-used commands can be abbreviated with an alias:

```
% alias uc=uncompress
% ls
hanoi.Z
% uc hanoi
% ls
hanoi
```

or commands with certain desired options:

```
% alias fm='finger -m'
% fm root
Login name: root                        In real life: Operator
Directory: /                            Shell: /bin/csh
On since May 19 10:41:15 on console     3 days 5 hours Idle Time
No unread mail
No Plan.

% alias lock='lock -p -60000'
% lock
lock: /dev/ttyr4 on phoenix. timeout in 60000 minutes
time now is Fri May 24 04:23:18 EDT 1991
Key:

% alias l='ls -AF'
% l /
.bash_history             kadb*
.bashrc                   lib@
.cshrc                    licensed/
.exrc                     lost+found/
.login                    macsyma
```

Aliases can also be used to replace old commands:

```
% alias grep=egrep ps=sps make=gmake
% alias whoami='echo root'
% whoami
root
```

or to define new ones:

```
% cd /
% alias sz='ls -l | sort -n +3 | tail -10'
% sz
drwxr-sr-x  7 bin          3072 May 23 11:59 etc
drwxrwxrwx 26 root         5120 May 24 04:20 tmp
drwxr-xr-x  2 root         8192 Dec 26 19:34 lost+found
drwxr-sr-x  2 bin         14848 May 23 18:48 dev
-r--r--r--  1 root       140520 Dec 26 20:08 boot
-rwxr-xr-x  1 root       311172 Dec 26 20:08 kadb
-rwxr-xr-x  1 root      1209695 Apr 16 15:33 vmunix.old
-rwxr-xr-x  1 root      1209702 May 14 19:04 vmunix
-rwxr-xr-x  1 root      1209758 May 21 12:23 vmunix.new.kernelmap.old
-rwxr-xr-x  1 root      1711848 Dec 26 20:08 vmunix.org
% cd
% alias rable='ls -AFtrd *(R)' nrable='ls -AFtrd *(^R)'
% rable
README      func/       bin/        pub/        News/       src/
nicecolors  etc/        scr/        tmp/        iris/       zsh*
% nrable
Mailboxes/  mail/       notes
```

(The pattern `*(R)` matches all readable files in the current directory, and `*(^R)` matches all unreadable files.)

Most other shells have aliases of this kind (*command* aliases). However, zsh also has *global* aliases, which are substituted anywhere on a line. Global aliases can be used to abbreviate frequently-typed usernames, hostnames, etc.

```
% alias -g me=pfalstad gun=egsirer mjm=maruchck
% who | grep me
pfalstad ttyp0   May 24 03:39   (mickey.Princeton)
pfalstad ttyp5   May 24 03:42   (mickey.Princeton)
% fm gun
Login name: egsirer                     In real life: Emin Gun Sirer
Directory: /u/egsirer                   Shell: /bin/sh
Last login Thu May 23 19:05 on ttyq3 from bow.Princeton.ED
New mail received Fri May 24 02:30:28 1991;
  unread since Fri May 24 02:30:27 1991
% alias -g phx=phoenix.princeton.edu warc=wuarchive.wustl.edu
% ftp warc
Connected to wuarchive.wustl.edu.
```

Here are some more interesting uses.

```
% alias -g M='| more' GF='| fgrep -f ~/.friends'
% who M    # pipes the output of who through more
% who GF   # see if your friends are on
% w GF     # see what your friends are doing
```

Another example makes use of zsh's process substitution. If you run NIS, and you miss being able to do this:

```
% grep pfalstad /etc/passwd
```

you can define an alias that will seem more natural than `ypmatch pfalstad passwd`:

```
% alias -g PASS='<(ypcat passwd)'
% grep pfalstad PASS
pfalstad:*:3564:35:Paul John Falstad:/u/pfalstad:/usr/princeton/bin/zsh
```

If you're really crazy, you can even call it `/etc/passwd`:

```
% alias -g /etc/passwd='<(ypcat passwd)'
% grep pfalstad /etc/passwd
pfalstad:*:3564:35:Paul John Falstad:/u/pfalstad:/usr/princeton/bin/zsh
```

The last example shows one of the perils of global aliases; they have a lot of potential to cause confusion. For example, if you defined a global alias called `|` (which is possible), zsh would begin to act very strangely; every pipe symbol would be replaced with the text of your alias. To some extent, global aliases are like macros in C; discretion is advised in using them and in choosing names for them. Using names in all caps is not a bad idea, especially for aliases which introduce shell metasyntax (like `M` and `GF` above).

Note that zsh aliases are not like csh aliases. The syntax for defining them is different, and they do not have arguments. All your favorite csh aliases will probably not work under zsh. For example, if you try:

```
alias rm mv '\!* /tmp/wastebasket'
```

no aliases will be defined, but zsh will not report an error. In csh, this line defines an alias that makes `rm` safe---files that are `rm`'d will be moved to a temporary directory instead of instantly destroyed. In zsh's syntax, however, this line asks the shell to print any existing alias definitions for `rm`, `mv`, or `!* /tmp/wastebasket`. Since there are none, most likely, the shell will not print anything, although `alias` will return a nonzero exit code. The proper syntax is this:

```
alias rm='mv \!* /tmp/wastebasket'
```

However, this won't work either:

```
% rm foo.dvi
zsh: no matches found: !*
```

While this makes `rm` safe, it is certainly not what the user intended. In zsh, you must use a shell function for this:

```
% unalias rm
% rm () { mv $* /tmp/wastebasket }
% rm foo.dvi
% ls /tmp/wastebasket
foo.dvi
```

While this is much cleaner and easier to read (I hope you will agree), it is not csh-compatible. Therefore, a script to convert csh aliases and variables has been provided. You should only need to use it once, to convert all your csh aliases and parameters to zsh format:

```
% csh
csh> alias
l       ls -AF
more    less
on      last -2 !:1 ; who | grep !:1
csh> exit
% c2z >neat_zsh_aliases
% cat neat_zsh_aliases
alias l='ls -AF'
alias more='less'
on () { last -2 $1 ; who | grep $1 }
...
```

The first two aliases were converted to regular zsh aliases, while the third, since it needed to handle arguments, was converted to a function. `c2z` can convert most aliases to zsh format without any problems. However, if you're using some really arcane csh tricks, or if you have an alias with a name like `do` (which is reserved in zsh), you may have to fix some of the aliases by hand.

The `c2z` script checks your csh setup, and produces a list of zsh commands which replicate your aliases and parameter settings as closely as possible. You could include its output in your startup file, `.zshrc`.

History

There are several ways to manipulate history in zsh. One way is to use csh-style `!` history:

```
% /usr/local/bin/!:0 !-2*:s/foo/bar/ >>!$
```

If you don't want to use this, you can turn it off by typing `setopt nobanghist`.

Another way is to use the `fc` command. For example, if you type an erroneous command:

```
% for i in ‘cat /etc/clients‘
 do
 rpu $i
 done
zsh: command not found: rpu
zsh: command not found: rpu
zsh: command not found: rpu
```

typing `fc` will execute an editor on this command, allowing you to fix it. (The default editor is `vi`, by the way, not `ed`).

```
% fc
49
/rpu/s//rup/p
 rup $i
w
49
q
for i in ‘cat /etc/clients‘
 do
 rup $i
 done
        beam    up  2 days, 10:17,    load average: 0.86, 0.80, 0.50
         bow    up  4 days,  8:41,    load average: 0.91, 0.80, 0.50
        burn    up          17:18,    load average: 0.91, 0.80, 0.50
       burst    up  9 days,  1:49,    load average: 0.95, 0.80, 0.50
         tan    up          11:14,    load average: 0.91, 0.80, 0.50
       bathe    up  3 days, 17:49,    load average: 1.84, 1.79, 1.50
        bird    up  1 day,   9:13,    load average: 1.95, 1.82, 1.51
      bonnet    up  2 days, 21:18,    load average: 0.93, 0.80, 0.50
```

A variant of the `fc` command is `r`, which redoes the last command, with optional changes:

```
% echo foo
foo
% r
echo foo
foo

% echo foo
foo
% r foo=bar
echo bar
bar
```

Command Line Editing

zsh's command line editor, **ZLE**, is quite powerful. It is designed to emulate either emacs or vi; the default is emacs. To set the bindings for vi mode, type `bindkey -v`.

In addition to basic editing, the shell allows you to recall previous lines in the history. In emacs mode, this is done with *^P* (control-P):

```
% ls ~
-           README      file        mail        pub         tmp
Mailboxes   bin         func        nicecolors  scr         zsh
News        etc         iris        notes       src
% echo foobar
foobar
% ^P
% echo foobar^P
% ls ~_
```

Pressing *^P* once brings up the previous line (`echo foobar`); pressing it again brings up the line before that (`ls ~`). The cursor is left at the end of the line, allowing you to edit the line if desired before executing it. In many cases, **ZLE** eliminates the need for the `fc` command, since it is powerful enough to handle even multiline commands:

```
% for i in a b c d e
> do
> echo $i
> done
a
b
c
d
e
% ^P
% for i in a b c d e
 do
 echo $i
 done_
```

Now you can just move up to the part you want to change...

```
% for i in a b c d e
 do
 echo $i
 done
```

change it, and execute the new command.

```
% for i in f g h i j
 do
 echo $i
 done
f
g
h
i
j
```

Also, you can search the history for a certain command using *ESC-P*:

```
% set ESC-P
% setopt autolist ESC-P
% setopt nocorrect_
```

Another way is to do an incremental search, emacs-style:

```
% ^R
% _
i-search:

% ls /usr/bin
i-search: l

% date > foofilei
i-search: le
```

Another useful feature of the editor is command and filename completion.

```
% compTAB
% compress _

% ls /nicTAB
% ls /nicecolors _

% ls /usr/prTAB
% ls /usr/princeton/_

% ls -l =comTAB
% ls -l =compress _
```

If the completion is ambiguous, the editor will beep. You can list possible completions by pressing ^D:

```
% ls /vmuTAB —beep—
% ls /vmunix_
% ls /vmunix^D
vmunix                    vmunix.old
vmunix.new.kernelmap.old  vmunix.org
```

Or, you could just set the *AUTOLIST* option:

```
% setopt autolist
% ls /vmuTAB —beep—
vmunix                    vmunix.old
vmunix.new.kernelmap.old  vmunix.org
% ls /vmunix_
```

Another option you could set is *RECEXACT*, which causes exact matches to be accepted, even if there are other possible completions:

```
% setopt recexact
% ls /vmuTAB —beep—
vmunix                    vmunix.old
vmunix.new.kernelmap.old  vmunix.org
% ls /vmunix_TAB
% ls /vmunix _
```

The *fignore* variable lists suffixes of files to ignore during completion.

```
% ls fooTAB —beep—
foofile.c  foofile.o
% fignore=( .o \~ .bak .junk )
% ls fooTAB
% ls foofile.c _
```

Since `foofile.o` has a suffix that is in the `fignore` list, it was not considered a possible completion of `foo`.

Username completion is also supported:

```
% ls ~pfalTAB
% ls ~pfalstad/_
```

and parameter name completion:

```
% echo $ORGTAB
% echo $ORGANIZATION _
```

and hostname completion, if you give the shell a list of hosts to complete:

```
% hosts=( phoenix.princeton.edu uunet.uu.net nic.ddn.mil
> diskfarm.princeton.edu gnu.ai.mit.edu
> eniac.seas.upenn.edu )
% telnet diskTAB
% telnet diskfarm.princeton.edu _

% ftp uuTAB
% ftp uunet.uu.net _

% mail subbarao@phTAB
% mail subbarao@phoenix.princeton.edu _
```

and option completion:

```
% setopt noclTAB
% setopt noclobber _
```

and binding completion:

```
% bindkey '^X^X' puTAB
% bindkey '^X^X' push-line _
```

The `compctl` command is used to control how completion works. For example, to specify that certain commands show take commands as arguments, you use `compctl -c`:

```
% compctl -c man nohup
% man uptTAB
% man uptime _
```

To specify that a command should complete filenames, you should use `compctl -f`. This is the default. It can be combined with `-c`, as well.

```
% compctl -cf echo
% echo uptTAB
% echo uptime _

% echo foTAB
% echo foo.c
```

Similarly, use `-h` to specify hostnames, `-o` to specify options, `-v` to specify variables, and `-b` to specify bindings.

```
% compctl -h rlogin
% compctl -hfc rsh
% compctl -b bindkey
```

You can also use `-k` to specify a custom list of keywords to use in completion.

```
% ftphosts=(ftp.uu.net wuarchive.wustl.edu)
% compctl -k ftphosts ftp
% ftp wuTAB
% ftp wuarchive.wustl.edu _

% friends=(cpirazzi subbarao sukthnkr)
% compctl -k friends mail finger su
% finger cpTAB
% finger cpirazzi _
```

In addition to completion, *TAB* performs expansion if possible.

```
% ls *.cTAB
% ls foofile.c fortune.c rnd.c strfile.c unstr.c_
```

For example, suppose you have a bunch of weird files in an important directory:

```
% ls
  * * *       ; & % $??foo  dspfok        foo.c
  !"foo"!       ‘ \ ‘         foo           rrr
```

You want to remove them, but you don’t want to damage `foo.c`. Here is one way to do this:

```
% rm *TAB
% rm \ \ \*\ \*\ \*\ \ \  \!\"foo\"\! \;\ \&\ %\ \$’
’foo \‘\ \\\ \‘ dspfok foo foo.c rrr_
```

When you expand `*`, zsh inserts the names of all the files into the editing buffer, with proper shell quoting. Now, just move back and remove `foo.c` from the buffer:

```
% rm \ \ \*\ \*\ \*\ \ \  \!\"foo\"\! \;\ \&\ %\ \$’
’foo \‘\ \\\ \‘ dspfok foo rrr
```

and press return. Everything except `foo.c` will be deleted from the directory.

Here’s another trick; let’s say you have typed this command in:

```
% gcc -o x.out foob.c -g -Wpointer-arith -Wtrigraphs_
```

and you forget which library you want. You need to escape out for a minute and check by typing `ls /usr/lib`, or some other such command; but you don’t want to retype the whole command again, and you can’t press return now because the current command is incomplete. In zsh, you can put the line on the *buffer stack*, using *ESC-Q*, and type some other commands. The next time a prompt is printed, the `gcc` line will be popped off the stack and put in the editing buffer automatically; you can then enter the proper library name and press return (or, *ESC-Q* again and look for some other libraries whose names you forgot).

A similar situation: what if you forget the option to gcc that finds bugs using AI techniques? You could either use *ESC-Q* again, and type `man gcc`, or you could press *ESC-H*, which essentially does the same thing; it puts the current line on the buffer stack, and executes the command `run-help gcc`, where `run-help` is an alias for `man`.

Another interesting command is *ESC-A*. This executes the current line, but retains it in the buffer, so that it appears again when the next prompt is printed. Also, the cursor stays in the same place. This is useful for

executing a series of similar commands:

```
% cc grok.c -g -lc -lgl -lsun -lmalloc -Bstatic -o b.out
% cc fubar.c -g -lc -lgl -lsun -lmalloc -Bstatic -o b.out
% cc fooble.c -g -lc -lgl -lsun -lmalloc -Bstatic -o b.out
```

The *ESC-'* command is useful for managing the shell's quoting conventions. Let's say you want to print this string:

```
don't do that; type 'rm -rf \*', with a \ before the *.
```

All that is necessary is to type it into the editing buffer:

```
% don't do that; type 'rm -rf \*', with a \ before the *.
```

press *ESC-'* (escape-quote):

```
% 'don'\''t do that; type '\''rm -rf \*'\'', with a \ before the *.'
```

then move to the beginning and add the `echo` command.

```
% echo 'don'\''t do that; type '\''rm -rf \*'\'', with a \ before the *.'
don't do that; type 'rm -rf \*', with a \ before the *.
```

Let's say you want to create an alias to do this `echo` command. This can be done by recalling the line with *^P* and pressing *ESC-'* again:

```
% 'echo '\''don'\''\'\'''\''t do that; type '\''\'\'''\''rm -rf
\*'\''\'\'''\'', with a \ before the *.'\'''
```

and then move to the beginning and add the command to create an alias.

```
% alias zoof='echo '\''don'\''\'\'''\''t do that; type '\''\'\'''\''rm
-rf \*'\''\'\'''\'', with a \ before the *.'\'''
% zoof
don't do that; type 'rm -rf \*', with a \ before the *.
```

Another interesting option is *MENUCOMPLETE*. This affects the way *TAB* works. Let's look at the `/vmunix` example again:

```
% setopt menucomplete
% ls /vmu<TAB>
% ls /vmunix<TAB>
% ls /vmunix.new.kernelmap.old<TAB>
% ls /vmunix.old_
```

Each time you press *TAB*, it displays the next possible completion. In this way, you can cycle through the possible completions until you find the one you want.

The *AUTOMENU* option makes a nice compromise between this method of completion and the regular method. If you set this option, pressing the *TAB* key repeatedly after an ambiguous completion will cycle through the possible completions.

Bindings

Each of the above editor commands was actually a function bound by default to a certain key. The real names of the commands are:

`expand-or-complete`	*TAB*
`push-line`	*ESC-Q*
`run-help`	*ESC-H*
`accept-and-hold`	*ESC-A*
`quote-line`	*ESC-'*

These bindings are arbitrary; you could change them if you want. For example, to bind `accept-line` to ^Z:

```
% bindkey '^Z' accept-line
```

Another idea would be to bind the delete key to `delete-char`; this might be convenient if you use *^H* for backspace.

```
% bindkey '^?' delete-char
```

Or, you could bind *^X^H* to `run-help`:

```
% bindkey '^X^H' run-help
```

Other examples:

```
% bindkey '^X^Z' universal-argument
% bindkey ' ' magic-space
% bindkey -s '^T' 'uptime
> '
```

`universal-argument` multiplies the next command by 4. Thus *^X^Z^W* might delete the last four words on the line. If you bind space to `magic-space`, then csh-style history expansion is done on the line whenever you press the space bar.

The `-s` flag to `bindkey` specifies that you are binding the key to a string, not a command. Thus `bindkey -s '^T' 'uptime\n'` lets you VMS lovers get the load average whenever you press *^T*.

If you have a NeXT keyboard, the one with the `|` and `\` keys very inconveniently placed, the following bindings may come in handy:

```
% bindkey -s '\e/' '\\'
% bindkey -s '\e=' '|'
```

Now you can type *ALT-/* to get a backslash, and *ALT-=* to get a vertical bar. This only works inside zsh, of course; `bindkey` has no effect on the key mappings inside `talk` or `mail`, etc.

Another use of the editor is to edit the value of variables. For example, an easy way to change your path is to use the `vared` command:

```
% vared PATH
> /u/pfalstad/scr:/u/pfalstad/bin/sun4:/u/maruchck/scr:/u/subbarao/bin:/u/maruc
hck/bin:/u/subbarao/scripts:/usr/princeton/bin:/usr/ucb:/usr/bin:/bin:/usr/host
s:/usr/princeton/bin/X11:/./usr/lang:/./usr/etc:/./etc
```

You can now edit the path. When you press return, the contents of the edit buffer will be assigned to **PATH**.

Parameter Substitution

In zsh, parameters are set like this:

```
% foo=bar
% echo $foo
bar
```

Spaces before or after the `=` are frowned upon:

```
% foo = bar
zsh: command not found: foo
```

Also, `set` doesn't work for setting parameters:

```
% set foo=bar
% set foo = bar
% echo $foo

%
```

Note that no error message was printed. This is because both of these commands were perfectly valid; the `set` builtin assigns its arguments to the *positional parameters* (`$1`, `$2`, etc.).

```
% set foo=bar
% echo $1
foo=bar
% set foo = bar
% echo $3 $2
bar =
```

If you're really intent on using the csh syntax, define a function like this:

```
% set () {
>    eval "$1$2$3"
> }
% set foo = bar
% set fuu=brrr
% echo $foo $fuu
bar brrr
```

But then, of course you can't use the form of `set` with options, like `set -F` (which turns off filename generation). Also, the `set` command by itself won't list all the parameters like it should. To get around that you need a `case` statement:

```
% set () {
>    case $1 in
>    -*|+*|'') builtin set $* ;;
>    *) eval "$1$2$3" ;;
>    esac
> }
```

For the most part, this should make csh users happy.

The following sh-style operators are supported in zsh:

```
% unset null
% echo ${foo-xxx}
bar
% echo ${null-xxx}
xxx
% unset null
% echo ${null=xxx}
xxx
% echo $null
xxx
% echo ${foo=xxx}
bar
% echo $foo
bar
% unset null
% echo ${null+set}

% echo ${foo+set}
set
```

Also, csh-style `:` modifiers may be appended to a parameter substitution.

```
% echo $PWD
/home/learning/pf/zsh/zsh2.00/src
% echo $PWD:h
/home/learning/pf/zsh/zsh2.00
% echo $PWD:h:h
/home/learning/pf/zsh
% echo $PWD:t
src
% name=foo.c
% echo $name
foo.c
% echo $name:r
foo
% echo $name:e
c
```

The equivalent constructs in ksh (which are also supported in zsh) are a bit more general and easier to remember. When the shell expands `${foo#`*pat*`}`, it checks to see if *pat* matches a substring at the beginning of the value of `foo`. If so, it removes that portion of `foo`, using the shortest possible match. With `${foo##`*pat*`}`, the longest possible match is removed. `${foo%`*pat*`}` and `${foo%%`*pat*`}` remove the match from the end. Here are the ksh equivalents of the `:` modifiers:

```
% echo ${PWD%/*}
/home/learning/pf/zsh/zsh2.00
% echo ${PWD%/*/*}
/home/learning/pf/zsh
% echo ${PWD##*/}
src
% echo ${name%.*}
foo
% echo ${name#*.}
c
```

zsh also has upper/lowercase modifiers:

```
% xx=Test
% echo $xx:u
TEST
% echo $xx:l
test
```

and a substitution modifier:

```
% echo $name:s/foo/bar/
bar.c
% ls
foo.c    foo.h    foo.o    foo.pro
% for i in foo.*; mv $i $i:s/foo/bar/
% ls
bar.c    bar.h    bar.o    bar.pro
```

One possible source of confusion is the fact that in zsh, the result of parameter substitution is *not* split into words. Thus, this will not work:

```
% srcs='glob.c exec.c init.c'
% ls $srcs
glob.c exec.c init.c not found
```

This is considered a feature, not a bug. If splitting were done by default, as it is in most other shells, functions like this would not work properly:

```
$ ll () { ls -F $* }
$ ll 'fuu bar'
fuu not found
bar not found

% ll 'fuu bar'
fuu bar not found
```

Of course, a hackish workaround is available in sh (and zsh):

```
% setopt shwordsplit
% ll () { ls -F "$@" }
% ll 'fuu bar'
fuu bar not found
```

If you like the sh behaviour, zsh can accomodate you:

```
% ls ${=srcs}
exec.c  glob.c  init.c
% setopt shwordsplit
% ls $srcs
exec.c  glob.c  init.c
```

Another way to get the `$srcs` trick to work is to use an array:

```
% unset srcs
% srcs=( glob.c exec.c init.c )
% ls $srcs
exec.c  glob.c  init.c
```

or an alias:

```
% alias -g SRCS='exec.c glob.c init.c'
% ls SRCS
exec.c  glob.c  init.c
```

Another option that modifies parameter expansion is *RCEXPANDPARAM*:

```
% echo foo/$srcs
foo/glob.c exec.c init.c
% setopt rcexpandparam
% echo foo/$srcs
foo/glob.c foo/exec.c foo/init.c
% echo foo/${^srcs}
foo/glob.c foo/exec.c foo/init.c
% echo foo/$^srcs
foo/glob.c foo/exec.c foo/init.c
```

Shell Parameters

The shell has many predefined parameters that may be accessed. Here are some examples:

```
% sleep 10 &
[1] 3820
% echo $!
3820
% set a b c
% echo $#
3
% echo $ARGC
3
% ( exit 20 ) ; echo $?
20
% false; echo $status
1
```

($? and `$status` are equivalent.)

```
% echo $HOST $HOSTTYPE
dendrite sun4
% echo $UID $GID
701 60
% cd /tmp
% cd /home
% echo $PWD $OLDPWD
/home /tmp
% ls $OLDPWD/.getwd
/tmp/.getwd
```

`~+` and `~-` are short for `$PWD` and `$OLDPWD`, respectively.

```
% ls ~-/.getwd
/tmp/.getwd
% ls -d ~+/learning
/home/learning
% echo $RANDOM
4880
% echo $RANDOM
11785
% echo $RANDOM
2062
% echo $TTY
/dev/ttyp4
% echo $VERSION
zsh v2.00.03
% echo $USERNAME
pf
```

The `cdpath` variable sets the search path for the `cd` command. If you do not specify `.` somewhere in the path, it is assumed to be the first component.

```
% cdpath=( /usr ~ ~/zsh )
% ls /usr
5bin         dict         lang         net          sccs         sys
5include     etc          lector       nserve       services     tmp
5lib         export       lib          oed          share        ucb
adm          games        local        old          skel         ucbinclude
bin          geac         lost+found   openwin      spool        ucblib
boot         hosts        macsyma_417  pat          src          xpg2bin
demo         include      man          princeton    stand        xpg2include
diag         kvm          mdec         pub          swap         xpg2lib
% cd spool
/usr/spool
% cd bin
/usr/bin
% cd func
~/func
% cd
% cd pub
% pwd
/u/pfalstad/pub
% ls -d /usr/pub
/usr/pub
```

PATH and **path** both set the search path for commands. These two variables are equivalent, except that one is a string and one is an array. If the user modifies **PATH**, the shell changes **path** as well, and vice versa.

```
% PATH=/bin:/usr/bin:/tmp:.
% echo $path
/bin /usr/bin /tmp .
% path=( /usr/bin . /usr/local/bin /usr/ucb )
% echo $PATH
/usr/bin:.:/usr/local/bin:/usr/ucb
```

The same is true of **CDPATH** and **cdpath**:

```
% echo $CDPATH
/usr:/u/pfalstad:/u/pfalstad/zsh
% CDPATH=/u/subbarao:/usr/src:/tmp
% echo $cdpath
/u/subbarao /usr/src /tmp
```

In general, parameters with names in all lowercase are arrays; assignments to them take the form:

name`=(` *elem* ... `)`

Parameters with names in all uppercase are strings. If there is both an array and a string version of the same parameter, the string version is a colon-separated list, like **PATH**.

HISTFILE is the name of the history file, where the history is saved when a shell exits.

```
% zsh
phoenix% HISTFILE=/tmp/history
phoenix% SAVEHIST=20
phoenix% echo foo
foo
phoenix% date
Fri May 24 05:39:35 EDT 1991
phoenix% uptime
  5:39am  up 4 days, 20:02,  40 users,  load average: 2.30, 2.20, 2.00
phoenix% exit
% cat /tmp/history
HISTFILE=/tmp/history
SAVEHIST=20
echo foo
date
uptime
exit
% HISTSIZE=3
% history
   28  rm /tmp/history
   29  HISTSIZE=3
   30  history
```

In zsh, if you say

```
% >file
```

the command `cat` is normally assumed:

```
% >file
foo!
^D
% cat file
foo!
```

Thus, you can view a file simply by typing:

```
% <file
foo!
```

However, this is not csh or sh compatible. To correct this, change the value of the parameter **NULLCMD**, which is `cat` by default.

```
% NULLCMD=:
% >file
% ls -l file
-rw-r--r--  1 pfalstad        0 May 24 05:41 file
```

If `NULLCMD` is unset, the shell reports an error if no command is specified (like csh).

```
% unset NULLCMD
% >file
zsh: redirection with no command
```

Actually, **READNULLCMD** is used whenever you have a null command reading input from a single file. Thus, you can set **READNULLCMD** to `more` or `less` rather than `cat`. Also, if you set **NULLCMD** to `:` for sh compatibility, you can still read files with `< file` if you leave **READNULLCMD** set to `more`.

Prompting

The default prompt for zsh is:

```
phoenix% echo $PROMPT
%m%#
```

The `%m` stands for the short form of the current hostname, and the `%#` stands for a `%` or a `#`, depending on whether the shell is running as root or not. zsh supports many other control sequences in the **PROMPT** variable.

```
% PROMPT='%/> '
/u/pfalstad/etc/TeX/zsh>

% PROMPT='%~> '
~/etc/TeX/zsh>

% PROMPT='%h %~> '
6 ~/etc/TeX/zsh>
```

`%h` represents the number of current history event.

```
% PROMPT='%h %~ %M> '
10 ~/etc/TeX/zsh apple-gunkies.gnu.ai.mit.edu>

% PROMPT='%h %~ %m> '
11 ~/etc/TeX/zsh apple-gunkies>

% PROMPT='%h %t> '
12 6:11am>

% PROMPT='%n %w tty%l>'
pfalstad Fri 24 ttyp0>
```

Also available is the **RPROMPT** parameter. If this is set, the shell puts a prompt on the *right* side of the screen.

```
% RPROMPT='%t'
%                                                          6:14am

% RPROMPT='%~'
%                                                  ~/etc/TeX/zsh

% PROMPT='%l %T %m[%h] ' RPROMPT=' %~'
p0 6:15 phoenix[5]                                 ~/etc/TeX/zsh
```

These special escape sequences can also be used with the `-P` option to `print`:

```
% print -P %h tty%l
15 ttyp1
```

The **POSTEDIT** parameter is printed whenever the editor exits. This can be useful for termcap tricks. To highlight the prompt and command line while leaving command output unhighlighted, try this:

```
% POSTEDIT='echotc se'
% PROMPT='%S%% '
```

Login/logout watching

You can specify login or logout events to monitor by setting the **watch** variable. Normally, this is done by specifying a list of usernames.

```
% watch=( pfalstad subbarao sukthnkr egsirer )
```

The `log` command reports all people logged in that you are watching for.

```
% log
pfalstad has logged on p0 from mickey.
pfalstad has logged on p5 from mickey.
% ...
subbarao has logged on p8 from phoenix.
% ...
subbarao has logged off p8 from phoenix.
% ...
sukthnkr has logged on p8 from dew.
% ...
sukthnkr has logged off p8 from dew.
```

If you specify hostnames with an `@` prepended, the shell will watch for all users logging in from the specified host.

```
% watch=( @mickey @phoenix )
% log
djthongs has logged on q2 from phoenix.
pfalstad has logged on p0 from mickey.
pfalstad has logged on p5 from mickey.
```

If you give a tty name with a `%` prepended, the shell will watch for all users logging in on that tty.

```
% watch=( %ttyp0 %console )
% log
root has logged on console from .
pfalstad has logged on p0 from mickey.
```

The format of the reports may also be changed.

```
% watch=( pfalstad gettes eps djthongs jcorr bdavis )
% log
jcorr has logged on tf from 128.112.176.3:0.
jcorr has logged on r0 from 128.112.176.3:0.
gettes has logged on p4 from yo:0.0.
djthongs has logged on pe from grumpy:0.0.
djthongs has logged on q2 from phoenix.
bdavis has logged on qd from BRUNO.
eps has logged on p3 from csx30:0.0.
pfalstad has logged on p0 from mickey.
pfalstad has logged on p5 from mickey.
% WATCHFMT='%n on tty%l from %M'
% log
jcorr on ttytf from 128.112.176.3:0.
jcorr on ttyr0 from 128.112.176.3:0.
gettes on ttyp4 from yo:0.0
djthongs on ttype from grumpy:0.0
djthongs on ttyq2 from phoenix.Princeto
bdavis on ttyqd from BRUNO.pppl.gov
eps on ttyp3 from csx30:0.0
pfalstad on ttyp0 from mickey.Princeton
pfalstad on ttyp5 from mickey.Princeton
% WATCHFMT='%n fm %m'
% log
jcorr fm 128.112.176.3:0
jcorr fm 128.112.176.3:0
gettes fm yo:0.0
djthongs fm grumpy:0.0
djthongs fm phoenix
bdavis fm BRUNO
eps fm csx30:0.0
pfalstad fm mickey
pfalstad fm mickey
% WATCHFMT='%n %a at %t %w.'
% log
jcorr logged on at 3:15pm Mon 20.
jcorr logged on at 3:16pm Wed 22.
gettes logged on at 6:54pm Wed 22.
djthongs logged on at 7:19am Thu 23.
djthongs logged on at 7:20am Thu 23.
bdavis logged on at 12:40pm Thu 23.
eps logged on at 4:19pm Thu 23.
pfalstad logged on at 3:39am Fri 24.
pfalstad logged on at 3:42am Fri 24.
```

If you have a `.friends` file in your home directory, a convenient way to make zsh watch for all your friends is to do this:

```
% watch=( $(< ~/.friends) )
% echo $watch
subbarao maruchck root sukthnkr ...
```

If watch is set to `all`, then all users logging in or out will be reported.

Options

Some options have already been mentioned; here are a few more:

```
% cd /
% setopt autocd
% bin
% pwd
/bin
% ../etc
% pwd
/etc
```

Using the *AUTOCD* option, you can simply type the name of a directory, and it will become the current directory.

```
% setopt cdablevars
% foo=/tmp
% cd foo
/tmp
```

With *CDABLEVARS*, if the argument to `cd` is the name of a parameter whose value is a valid directory, it will become the current directory.

CORRECT turns on spelling correction for commands, and the *CORRECTALL* option turns on spelling correction for all arguments.

```
% setopt correct
% sl
zsh: correct ‘sl’ to ‘ls’ [nyae]? y
% setopt correctall
% ls x.v11r4
zsh: correct ‘x.v11r4’ to ‘X.V11R4’ [nyae]? n
/usr/princton/src/x.v11r4 not found
% ls /etc/paswd
zsh: correct to ‘/etc/paswd’ to ‘/etc/passwd’ [nyae]? y
/etc/passwd
```

If you press `y` when the shell asks you if you want to correct a word, it will be corrected. If you press `n`, it will be left alone. Pressing `a` aborts the command, and pressing `e` brings the line up for editing again, in case you agree the word is spelled wrong but you don’t like the correction.

Normally, a quoted expression may contain a newline:

```
% echo ’
> foo
> ’

foo

%
```

With *CSHJUNKIEQUOTES* set, this is illegal, as it is in csh.

```
% setopt cshjunkiequotes
% ls ’foo
zsh: unmatched ’
```

GLOBDOTS lets files beginning with a `.` be matched without explicitly specifying the dot.

```
% ls -d *x*
Mailboxes
% setopt globdots
% ls -d *x*
.exrc         .pnewsexpert  .xserverrc
.mushexpert   .xinitrc      Mailboxes
```

HISTIGNOREDUPS prevents the current line from being saved in the history if it is the same as the previous one; *HISTIGNORESPACE* prevents the current line from being saved if it begins with a space.

```
% PROMPT='%h> '
39> setopt histignoredups
40> echo foo
foo
41> echo foo
foo
41> echo foo
foo
41> echo bar
bar
42> setopt histignorespace
43>  echo foo
foo
43>  echo fubar
fubar
43>  echo fubar
fubar
```

IGNOREBRACES turns off csh-style brace expansion.

```
% echo x{y{z,a},{b,c}d}e
xyze xyae xbde xcde
% setopt ignorebraces
% echo x{y{z,a},{b,c}d}e
x{y{z,a},{b,c}d}e
```

IGNOREEOF forces the user to type `exit` or `logout`, instead of just pressing *^D*.

```
% setopt ignoreeof
% ^D
zsh: use 'exit' to exit.
```

INTERACTIVECOMMENTS turns on interactive comments; comments begin with a `#`.

```
% setopt interactivecomments
% date # this is a comment
Fri May 24 06:54:14 EDT 1991
```

NOCLOBBER prevents you from accidentally overwriting an existing file.

```
% setopt noclobber
% cat /dev/null >~/.zshrc
zsh: file exists: /u/pfalstad/.zshrc
```

If you really do want to clobber a file, you can use the `>!` operator. To make things easier in this case, the `>` is stored in the history list as a `>!`:

```
% cat /dev/null >! ~/.zshrc
% cat /etc/motd > ~/.zshrc
zsh: file exists: /u/pfalstad/.zshrc
% !!
cat /etc/motd >! ~/.zshrc
% …
```

RCQUOTES lets you use a more elegant method for including single quotes in a singly quoted string:

```
% echo ’"don’\’’t do that."’
"don’t do that."
% echo ’"don’’t do that."’
"dont do that."
% setopt rcquotes
% echo ’"don’’t do that."’
"don’t do that."
```

Finally, *SUNKEYBOARDHACK* wins the award for the strangest option. If a line ends with `‘`, and there are an odd number of them on the line, the shell will ignore the trailing `‘`. This is provided for keyboards whose RETURN key is too small, and too close to the `‘` key.

```
% setopt sunkeyboardhack
% date‘
Fri May 24 06:55:38 EDT 1991
```

Closing Comments

I would be happy to receive mail if anyone has any tricks or ideas to add to this document, or if there are some points that could be made clearer or covered more thoroughly. Please notify me of any errors in this document.